

DAWN

MINI

AUSTRALIA & NEW ZEALAND'S FAVOURITE BLOCKOUT

Vibrant, happy, young and energised, that's how Dawn Mini can be summed up. Based on a palette of bright and cheerful colours such as Apple Fizz, Baby Doll, Fairy Dust, Fire Engine, Periwinkle, Sunshine, Surf Safari and Tang, who couldn't feel good about those? Ideally suited to kid's rooms, kindergartens, day care centres and paediatric rooms, Dawn Mini will brighten any day.

AS AN EXTENSION OF THE DAWN RANGE, MINI FEATURES INCLUDE:

- An unsurpassed 10 Year Fabric Warranty!
- Greenguard Gold Certification ensures that Dawn has a low level of chemical emissions which significantly improves the quality of the air.
- Ultra-Fresh antimicrobial additives control the growth of unwanted microbes and guarantees continuous odour control and fabric protection against mould, mildew and stain causing bacteria.
- The Uniguard fabric protection system improves the durability of our fabrics by making them easier to maintain and clean.
- Oeko-Tex accreditation ensures that there are no harmful substances used during the manufacturing process.



DAWN MINI

AUSTRALIA & NEW ZEALAND'S
FAVOURITE BLOCKOUT



TECHNICAL SPECIFICATIONS – DAWN MINI

APPLICATION:

PANEL GLIDE	✓
ROLLER	✓
ROMAN	
VERTICAL	✓

FABRIC TYPE:

BLOCKOUT	✓
TRANSLUCENT	
SCREEN	

CARE: Surface dust should be removed with a duster or soft cloth. Fabric can be wiped with a damp sponge and wiped with a soft cloth. Never use abrasive or solvent-based products.

NOTE: Refer to Uniline website for up to date fabric and swatch information.

SPECIFICATIONS:

AIR QUALITY	Greenguard® certified to guarantee Air Purity
WARRANTY	Unsurpassed 10 Year fabric Warranty
PROTECTION	Ultra-Fresh® Antimicrobial Mould & Mildew Resistant
OPACITY	All colours are 100% Blockout AS-2663.3-1999
LIGHT FASTNESS	Fully Fade Resistant: Result 6-7 ISO 105-B02:1994 (Xenon Arc Method)
COMPOSITION	100% Polyester
COATING	Acrylic – PVC free
FIRE RETARDANCY	Complies with General Requirements of the Building Code of Australia for Fire Hazard Properties of materials used. Not suitable for use in parts of buildings with special requirements. Tested to AS1530.2 & 1530.3. Test reports available on request.
WEIGHT	375gsm
THICKNESS	0.39mm
WIDTHS	127mm and 3.0mtr.



IT'S YOUR CHOICE.

The preferred window covering system supplier to the industry.

Australia Free Call: 1800 777 331 | sales@uniline.com.au | uniline.com.au

New Zealand Free Call: 0800 700 801 | salesnz@uniline.com.au | uniline.co.nz

