# TEMPO

# SUBTLETY OF DAPPLED LANDSCAPE

Inspired by the subtlety of dappled landscape colours in hues ranging from the Arctic to the Kalahari, we have combined classic design with a soft and delicate fabric texture. Our design philosophy for Tempo is "Less is More".

With its timeless appeal, we are confident that Tempo will suit any window from a stylish contemporary apartment to a heritage home.

#### **KEY FEATURES ARE:**

- 3 metre width.
- 8 colours in blockout.
- Matching colours in light filtering.
- Mould and mildew protection system.
- Uniline quality.















# TEMPO



# SUBTLETY OF DAPPLED LANDSCAPE

#### **BLOCK OUT**

| Linen | Cotton | Wheat | Oatmeal | Mink | Pepper | Umber | Charcoal |
|-------|--------|-------|---------|------|--------|-------|----------|

### TRANSLUCENT

| Linen | Cotton | Wheat | Oatmeal | Mink | Pepper |
|-------|--------|-------|---------|------|--------|

#### **TECHNICAL SPECIFICATIONS - TEMPO**

#### APPLICATION:

| PANEL GLIDE | ✓ |
|-------------|---|
| ROLLER      | ✓ |
| ROMAN       | ✓ |

#### **FABRIC TYPE:**

| The state of the s |   |
|--|---|
| BLOCKOUT   | ✓ |
| TRANSLUCENT  | ✓ |
| SCREEN   |   |

CARE: Surface dust should be removed with a duster or soft cloth. Fabric can be wiped with a damp sponge and wiped with a soft cloth. Never use abrasive or solvent-based products.

**NOTE:** Refer to Uniline website for up to date fabric and swatch information.

#### SPECIFICATIONS:

|                               | BLOCKOUT   | TRANSLUCENT  |  |
|-------------------------------|--|--|--|
| WARRANTY                      | 5 Year fabric Warranty   | 5 Year fabric Warranty   |  |
| MOULD & MILDEW<br>PROTECTION  | Yes  | Yes  |  |
| LIGHT FASTNESS                | Fully Fade Resistant: Result 5-6<br>ISO 105-B02:1994<br>(Xenon Arc Method) | Fully Fade Resistant: Result 5-6<br>ISO 105-B02:1994<br>(Xenon Arc Method) |  |
| COMPOSITION                   | 90% Polyester,<br>10% Cationic Polyester                                   | 90% Polyester,<br>10% Cationic Polyester                                   |  |
| BLOCKOUT                      | Yes  | No   |  |
| WEIGHT                        | 405gsm   | 210gsm   |  |
| THICKNESS                     | 0.55mm   | 0.38mm   |  |
| WIDTH                         | 3.0mtr   | 3.0mtr   |  |
| ROLL LENGTH 20mtr             |  | 25mtr  |  |
| RECOMMENDED<br>CUTTING METHOD | Ultrasonic, Crush Cutter, Blade  | Ultrasonic   |  |





## IT'S YOUR CHOICE.

The preferred window covering system supplier to the industry.

Australia Free Call: 1800 777 331 | sales@uniline.com.au | uniline.com.au New Zealand Free Call: 0800 700 801 | sales@uniline.co.nz | uniline.co.nz

