

UNIVIEW

2%, 5% & 10% INTERIOR SCREEN FABRIC

MORE LIGHT, BETTER VIEW AND DAY PRIVACY

Functional design never dates, and that goes for Uniview Interior Screen fabrics. Now available in 17 common colours in a 2%, 5% and 10% openness factor.

We have a solution for all of your windows regardless of aspect. For instance, if you have a western facing window and you want to reduce heat and glare but maintain your outlook, then choose Uniview 2%. If you have a south facing window and want to let as much light in as possible then Uniview 10% would suit; and for everything in between you can't go past Uniview 5%.

Uniview Interior Screen options have varying degrees* of UV protection, great news if you want to help protect your carpet and soft furnishings from fading in the harsh Australian sun.

They are also flame resistant and come with an unsurpassed 10 year fabric warranty. For complete privacy at night, why not match with a co-ordinating Dawn Blockout colour in a dual system? Every Uniview Interior colour now has a matching Dawn Blockout colour. We have even made it easier to match by including labels on the back of each swatch colour referencing the Dawn colour that it matches!

With its architectural looks and unrivalled quality, it's no wonder that Uniview Screen fabric is the choice of decorators and interior designers.

* Refer to Technical Specification



UNIVIEW



2%, 5% AND 10% INTERIOR SCREEN FABRIC

Chalk	Cream	Beige	Sandstone	Moss	Toffee	Mocca	Coffee Brown	New Slate	White	White Grey
Baltic	Grey	Black Grey	Charcoal	Storm	Black Ash					

TECHNICAL SPECIFICATIONS – UNIVIEW 2%, 5% AND 10%

APPLICATION:

PANEL GLIDE	✓
ROLLER	✓
ROMAN	
VERTICAL	

FABRIC TYPE:

BLOCKOUT	
TRANSLUCENT	
SCREEN	✓

CARE: Surface dust should be removed with a duster or soft cloth. Fabric can be wiped with a damp sponge and wiped with a soft cloth. Never use abrasive or solvent-based products.

NOTE: Refer to Uniline website for up to date fabric and swatch information.

SPECIFICATIONS:

AIR QUALITY	Greenguard® certified to guarantee Air Purity		
WARRANTY	Unsurpassed 10 Year fabric Warranty		
PROTECTION	Uniguard fabric protection system		
LIGHT FASTNESS	Fully Fade Resistant: Result 6-7 ISO 105-B02:1994 (Xenon Arc Method)		
COMPOSITION	75% PVC, 25% Polyester		
FIRE RETARDANCY	Complies with General Requirements of the Building Code of Australia for Fire Hazard Properties of materials used. Tested to AS1530.3. Test reports available on request.		
OPENNESS FACTOR	2%	5%	10%
WEIGHT	495gsm	430gsm	430gsm
THICKNESS	0.63mm	0.61mm	0.68mm
SHADE COVER	98%	95%	90%
WIDTH	3.0mtr	2.5mtr and 3.0mtr	3.0mtr
RECOMMENDED CUTTING METHOD	Ultrasonic, Crush Cutter		



IT'S YOUR CHOICE.

The preferred window covering system supplier to the industry.

Australia Free Call: 1800 777 331 | sales@uniline.com.au | uniline.com.au

New Zealand Free Call: 0800 700 801 | sales@uniline.co.nz | uniline.co.nz

