



WIRE GUIDE AWNING

PRODUCT DESCRIPTIONS

Impeccably constructed right down to the smallest detail, the Standard Wire Guide external awning by Uniline is your passport to sleek and modern-looking windows.



Maximum Width	5800mm
Maximum Drop	3500mm
Maximum Area	20sqm
Tube	63mm Roll Formed Zinalume® .75mm AZ150 (5600mm/6500mm) 63mm Thredbo White Powder Coated .75mm AZ150 (5600mm) 70mm Galvanised Locked Seam Z150 1.0mm (5800mm) 78mm Galvanised Locked Seam Z150 1.0mm (5800mm) 85mm Galvanised Locked Seam Z150 1.2mm (5800mm)
Drives	Manual Gearbox Geiger 2.7:1 Manual Gearbox Geiger 9:1 Automation – NICE 15nm ERAMAT Motors
Drive End	Nylon 66 (5% Glass Filled)
Idler with Hole	Nylon 66 (5% Glass Filled)
Universal Fixing Brackets	T304 Polished Stainless Steel Mild Steel Polyester Powder Coated Colours
Top Bush	T316 Stainless Steel
Pivot Pin & Plate	T304 Stainless Steel Mild Steel (Zinc Plated Service Condition 4)
Wire Guide Cable	3.2mm T316 Stainless Steel (19x1 construction)
Bottom Bush	T316 Stainless Steel
L Bracket	T304 Stainless Steel
Deck Plate	T304 Stainless Steel
Bottom Rail	Anodised Aluminium 6063 T5
End Cap Master & Guide	Nylon 66 (5% Glass Filled)

THE CHOICE IS YOURS

- Wire Guide can be face fit or ceiling mounted. Box in a balcony or pergola for year round shade or deflect sun from too-hot windows
- Customise your awning with fabric from the Uniview Outdoor or Unishade ranges by Uniline
- All components are corrosion resistant, ideal for coastal locations
- Manual, motorised or automated operation available. The automated system comes with wind and sun sensors that automatically adjust the awning according to weather conditions

IT'S YOUR CHOICE.

The preferred window covering system supplier to the industry.

Australia +61 7 3804 9000 | info@uniline.com.au | uniline.com.au

New Zealand +64 9 273 5026 | salesnz@uniline.com.au | uniline.co.nz

